

Architex®

CERTIFICATE OF FLAME RESISTANCE + SPECIFICATIONS

Architex International hereby certifies that the fabric described passes the following flame resistance specifications:

BRILLIANCE



© Architex 2026



Maintenance + Cleaning

WS. Acid, Alcohol, Ozone, Peroxide, Phenolic, Quaternary, UV-C - Based Cleanable

Consult a professional prior to cleaning. For ordinary cleaning, use mild soap and water. For more severe soiling, remove promptly with a non-abrasive cleaner. Gently lift any remaining spill to avoid further staining. Rub gently and rinse with water dampened cloth to remove cleaner concentration. Kindly spot test an area before cleaning.

Characteristics

Usage: Upholstery, Drapery, Room-Darkening

Width: 54" (137.16 cm)

Repeat: None

Content: 100% Polyester

Backing: None

Weight: 0.8 lb/ly (362.874 gr/lm)

Country Of Origin: China

Performance

Durability: 100,000 double rubs; Wyzenbeek

Finish: No Finish

Lightfastness: 40 hours; Method AATCC 16

Flammability: CAL TB 117-2013, NFPA 260/UFAC Class 1 , NFPA 701

Sustainability

AB 2998 Compliant

Antimicrobial Free

FR Free

Healthy Interiors Compliant

ISO 14001 Certified Facility

Oeko-Tex 100 Certified

PFAS Free

PVC Free

Proposition 65 Compliant

Red List Free

Warranty

See [Terms of Use and Sale](#) for more information.


Notes

Architex®

BRILLIANCE COLORWAYS



Aegean



Ash



Barley



Butterscotch



Celadon



Chestnut



Claret




Coal



Hazel



Jet



Kingfisher



Lagoon



Midnight



Moss



Oyster



Silver



Stone



Truffle